

AD-A120 732

FANSHAPED SUPERRADIANCE OF A DYE LASER(U) FOREIGN
TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH X WANG ET AL.
22 SEP 82 FTD-ID(RS)T-1239-82

1/1

UNCLASSIFIED


F/G 20/5 NL



END

FORM 1

11/81



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD A 120732

DTIC FILE COPY

FTD-ID(RS)T-1239-82

FOREIGN TECHNOLOGY DIVISION



FANSHAPED SUPERRADIANCE OF A DYE LASER

by

Wang Xipo, Peng Guifang



OCT 22 1982

A

Approved for public release;
distribution unlimited.

82 10 22 051

EDITED TRANSLATION

FTD-ID(RS)T-1239-82

22 September 1982

MICROFICHE NR: FTD-82-C-001252

FANSHAPED SUPERRADIANCE OF A DYE LASER

By: /Wang Xipo, /Peng Guifang

English pages: 2

Source: Jiguang, Vol. 9, Nr. 3, March 1982, pp. 174

Country of origin: China

Translated by: Randy Dorsey

Requester: FTD/TQCS

Approved for public release; distribution unlimited.

Classification For

UNCLASSIFIED

EXCLUDED

EXCLUDED

EXCLUDED



Classification

Classification Code

Available and/or

Excluded

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP.AFB, OHIO.

FTD-ID(RS)T-1239-82

Date 22 Sep 19 82

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

FANSHAPED SUPERRADIANCE OF A DYE LASER

Wang Xipo, Peng Guifang

Abstract: In this paper we report the fanshaped superradiance of the dye laser achieved by using second harmonics from a giant pulsed YAP:Nd^{3+} laser oscillator-amplifier to pump Rhodamine 6G.

In July, 1980, Professor Chen Ruiliang of Laval University in Canada came and gave lectures to us and introduced a recent Hungarian invention - the fanshaped laser. Recently, based on Professor Chen's introduction, we also achieved fanshaped superradiance of a dye laser. Since emissions of this kind of laser beam assume a fan shape which is planar and since it is amplified spontaneous emission, it is called a "fanshaped laser" or "fanshaped superradiance of a dye laser".

The experimental apparatus with which we achieved fanshaped superradiance of a dye laser is shown in Fig. 1.



Fig. 1. Experimental apparatus for dye laser fanshaped superradiance

KEY: 1. Total reflecting dielectric film ($1.079\mu\text{m}$); 2. Single 45° LiNbO_3 electrooptical Q-switching crystal; 3. Yttrium aluminate (YAP:Nd^{3+}) laser rod $\phi 5 \times 55\text{mm}$; 4. Flat glass output plate; 5. Optical isolator; 6. YAP laser amplifying rod $\phi 6 \times 70\text{mm}$; 7. Frequency doubling (SHG) LiIO_3 crystal; 8. Dichromatic film, for the fundamental wave ($1.079\mu\text{m}$) total reflection, for the harmonic ($0.539\mu\text{m}$) $T=90\%$; 9. Right-angle prism; 10. Dye reservoir.

The laser device employs a single 45° LiNbO_3 electrooptical

Q-switching yttrium aluminate laser as the oscillation stage, and after one stage of yttrium aluminate laser amplification, it puts out a laser peak power of approximately 30MW, with a repetition rate of once per second; using LiIO_3 (I type phase matching, $\theta_m \approx 30^\circ$) outer cavity frequency doubling, it puts out $0.539\mu\text{m}$ frequency doubled light, with a peak power of 1.8MW; and then using $0.539\mu\text{m}$ frequency doubled light to pump Rhodamine 6G laser dye, we achieved fanshaped superradiance of a dye laser.

In our experiments, the dye reservoir was an ordinary glass tube with a diameter of 12mm and a wall thickness of 1mm which had been made into a cylinder. It held Rhodamine 6G laser dye in an ethyl alcohol solution with a concentration of either 1.1×10^{-4} gram moles/liter or 1.1×10^{-3} gram moles/liter. The pumping light was pumped in through the bottom of the dye reservoir. Since at a very high pumping rate (pulse pumping duration $< 10\text{ns}$) the laser gain is sufficiently high, the major portion of the photon emission goes into an amplified spontaneous emission mode, that is, forms superradiance. As a result, the output is two symmetrical fanshaped, planar beams of light as shown in Figures 2 and 3.




Fig. 2. Schematic diagram of dye laser fanshaped superradiance

KEY: (a) μm



Fig. 3. Photograph of fanshaped superradiance of a dye laser.

The achievement of this kind of laser beam can be expected to have some specific uses in a number of fields.

Changchun Institute of Applied Chemistry, Chinese Academy of Sciences
Submitted 14 July 1981

END